

Strainer DN 25

Strainer with manual shut off

For coolant mixture of water and antifreeze



Hose nozzle 38 mm DIN 71 550
Operating pressure -0,5 to 4 bar

8498125.0000.00000
Origin Series 84900
05.06

Description

Switching Function: Manual operated shut off
Flow Direction: Determined
Fluid Temperature: - 30 °C - + 110 °C
Ambient Temperature: - 30 °C - + 110 °C
Mounting Position: Filter housing vertical underneath

Material

Body: PA 66
Seals: EPDM/HNBR
Internal Parts: PA 66, 1.4301

Features

- Filter mesh size 0.315 mm
- Manual override

Characteristic Data

DN [mm]	Con- nection	Operating Pressure with Fluids up to 40 mm ² /s (cSt) min. max.		Kv-Value Base: m ³ /h	Weight [kg]	Sectional-Drawing-No.	Cat.-No.	
							Valve	Solenoid
25	38 mm	-0,5	4	15	0,5	8498125.0000.00000	84 981 25.0000.00000	

Buschjost GmbH
Valve Technology and Systems

Detmolder Straße 256 Phone
D-32545 Bad Oeynhausen ++49 5731/791-0
PO Box 10 02 52-53 Fax
D-32502 Bad Oeynhausen ++49 5731/791-179

www.buschjost.com
mail@buschjost.com



(a)		28.03.2011		Norm. / Approved: 01.06.2011 S. Rehme Gepr. / Checked: 10.05.2011 S. Sticker																		
Art-Stand / Rev: 06 Art-Datum/Rev. Date:				Bearb.: / Drawn: 23.07.2003 Doan Datum / Date: Name																		
a 6835 28.03.2011 Bartelsmeier Art-Nr / Rev-Nr: Datum Date: Name																						
Erl. für / Inspection:		 Busch+jost		Für diese Zeichnung behalten wir uns alle Rechte vor. All rights reserved for this drawing.																		
Allgemeintoleranzen für Radlen, Fasern und Winkel nach ISO 2768-m																						
1:1																						
Benennung / Designation																						
<table><tr><td>über</td><td>200</td><td>+3</td></tr><tr><td>über</td><td>130 bis 200</td><td>+2,5</td></tr><tr><td>über</td><td>80 bis 130</td><td>+2</td></tr><tr><td>über</td><td>30 bis 80</td><td>+1,5</td></tr><tr><td>über</td><td>30</td><td>+1</td></tr><tr><td>über</td><td>30</td><td>+1</td></tr></table>		über	200	+3	über	130 bis 200	+2,5	über	80 bis 130	+2	über	30 bis 80	+1,5	über	30	+1	über	30	+1	Schmutzfänger Strainer		DIN A 2
über	200	+3																				
über	130 bis 200	+2,5																				
über	80 bis 130	+2																				
über	30 bis 80	+1,5																				
über	30	+1																				
über	30	+1																				
Ident-Nr. / Ident No.																						
Allgemeintoleranzen / General Tolerances		8498125.0000.00000																				